

ideuk Lubricants Specifications of Products

Industrial Gear Oil

● Product abstract

Super EP oil of **ideuk co., ltd.** is high-quality oil in AGMA EP standard that used high-quality oil of best-refined process and extreme pressure agent of sulfur-phosphorus group.

● Product characteristic

- Extreme pressure capacity is very higher.
- Use life is long because stability of oxidation is superior.
- Anti-rust and anti-caustic is superior.
- Anti-forming is superior.

● Product usage

- Closeness gear system, reduction gear, gear box etc.
- It uses to all lubricating device the high pressure gear oil is necessary.

● Specifications

Classification	Product	Specific Gravity 15/4℃	Kinematic Viscosity cSt, 40℃	Flash Point ℃	Viscosity Index	Pour Point ℃	Rust-preventing characteristic	Corrosive test (100℃ 3h)	Others
Industrial Gear Oil	Super EP 68	0.875	68.81	235	103	-12.5	pass	pass	
	Super EP 100	0.892	94.24	230	95	-15	pass	pass	
	Super EP 150	0.895	150	232	97	-15	pass	pass	
	Super EP 220	0.895	220	240	96	-15	pass	pass	
	Super EP 320	0.912	320	255	94	-15	pass	pass	
	Super EP 460	0.915	460	263	95	-15	pass	pass	

* The above is recently tested representative values and could be a little different within the limits of which can not be effected.

www.eduk.co.kr www.eduk.pe.kr e-mail : eduk@eduk.co.kr